



Olympia Micro™ *ClimaPlus*™



OLYMPIA MICRO Panels with *CLIMAPLUS* Superior Performance/
DONN Suspension System

ESD Information

Recycled Content: 52%
CLIMAPLUS Superior Performance for Mould/Mildew

★ Contributes to Green Star points ✓ ESD additional advantages

IEQ						Ene	Mat
Increase Daylight Levels	Reduce Lighting Levels	Internal Noise Level Reduction	Low Volatile Organic Compounds	Low Formaldehyde	Mould Prevention	Lighting Density Reduction	Design for Disassembly
★	★	★	✓	✓	✓	★	✓

Advantages

- Nondirectional pattern reduces installation time and waste.
- Economical, fine-textured panel.
- Excellent light reflectance enhances indirect lighting of a space.
- *CLIMAPLUS* 30-year lifetime system warranty to withstand conditions up to 40°C/95% relative humidity without visible sag when used with a *DONN*® brand suspension system.

Applications

- Classrooms
- Hotels
- Reception and lobby areas
- Restaurants
- Retail stores
- Offices

Substrate

- Water-felted mineral fibre



Fine-textured panel

Grid Options

DONN DX 24mm



DONN Certricitée 15mm



Olympia Micro™ ClimaPlus™

Information
 usg.com.au
 usg.co.nz
 info-anz@usg.co.nz

ESD Information
 greenusg.com.au
 greenusg.co.nz

30
 Year System Warranty
 - No visible sag
 - Mould/mildew protection

	Edge	Panel Size ^{1,2}	Class	Item No	NRC ³	CAC ³	LR ⁴	Colour	Grid Options	VOC Emissions	Anti-Mould & Mildew ⁵	Recycled Content
OLYMPIA Micro CLIMAPlus Panels	SQ 	600 x 600 x 15mm	Class A	ME4211	.50	35-39	.87	White	A	Low		52%
		1200 x 600 x 15mm	Class A	ME4411	.50	35-39	.87	White	A	Low		52%
	SLT 	600 x 600 x 15mm	Class A	ME4421	.50	35-39	.87	White	B	Low		52%
		1200 x 600 x 15mm	Class A	ME4421	.50	35-39	.87	White	B	Low		52%
	FLB 	1200 x 600 x 15mm	Class A	ME4231	.50	35-39	.87	White	C	Low		52%
OLYMPIA Micro CLIMAPlus Illusion Two/24 Panels	SLT 	1200 x 600 x 19mm	Class A	ME4742	.50	35-39	.87	White	B	Low		52%
	ILT 	1200 x 600 x 19mm	Class A	ME4744	.50	35-39	.87	White	D	Low		52%

Legend

Low Emissions (VOC Class)

Classified as low-emitting per standards established by the Collaborative for High-Performance Schools (CHPS), following California Specification 01350 testing methods. Low-emitting is defined as having less than 13.5 ppb.

CLIMAPlus Superior Performance

Contains a broad-spectrum antimicrobial treatment on the face and back of the panel that provides guaranteed resistance against the growth of mould/mildew.

A	B	C	D
DX®	DX	Centricitee DXT	Centricitee DXT

Grid Profile Options

Physical Data/ Footnotes

Weight
 3.8 kg/m² (15mm)
 5.0 kg/m² (19mm)

Environmental Limitations
 40°C, 95% RH max.

Thermal Resistance
 R 0.25m² °C/W (15mm)
 R 0.30m² °C/W (19mm)

Early Fire Performance

Index	Ignitability	Spread of Flame	Heat Evolved	Smoke Developed
AS/NZS 1530.3	0	0	0	3
ASTM E84	-	25	-	50
AS/NZS 3837	Group 1 – unsprinklered			

Maximum Backloading
 0 kg/m²

Maintenance
 Can be cleaned easily with a soft brush or vacuum

Footnotes

- Not all panel sizes available in all geographic areas
- Some imperial sizes available to order
- Acoustic Test Standards
 NRC to ASTM C423
 CAC to ASTM E1414
- LR values are shown as averages
- Panel face and back surfaces treated with a patented, broad-spectrum antimicrobial standard formulation that inhibits and retards the growth of mould/mildew.
- Trademarks used herein belong to USG Interiors, Inc or a related company

Safety First!

Follow good safety and industrial hygiene practices during handling and installing of all products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read material safety data sheets and related literature on products before specification and/or installation.



green building council australia
 MEMBER



USG Australasia

Queensland

Phone: (07) 3852 5937
 Fax: 1800 786-946 (free fax)

New South Wales

(02) 8850 3935
 1800 786-946 (free fax)

Victoria

(03) 9639 0900
 1800 786-946 (free fax)

Auckland Head Office

(09) 636 3680
 (09) 636 3679

Wellington

(04) 560 4528
 (04) 560 4529

OM/1-09